



HLD 1200_6000

HLD SERIES TECHNICAL PRECISION "TOP-LOADING" SCALE



Multifunctional scale, suitable for laboratory and industrial use. Available also CE-M APPROVED for legal for trade use.

DIVISION (g): from 0.02 to 0.1.

CAPACITY (g): 1200, 3000, 6000.

The best solution
for advanced industrial
applications

TECHNICAL FEATURES

- Backlit LCD display with 7 digits 16mm high.
- Waterproof membrane keypad, with acoustic feedback, with 7 keys.
- Stainless steel plate, size: 140x150mm.
- Level and adjustable feet.
- Built-in rechargeable battery (about 30h battery life) and 230 Vac mains power adapter.
- Operating temperature +5°C...+40°C.
- RS232/c port for connection to PC or printer (serial parameters not programmable in CE-M approved version).
- Packaging: 370x240x250mm size - approximate weight of 2,7kg.
- Upon request:
 - ACCREDIA calibration with issuing of relative certificate
 - CE-M approval in class II.

FUNCTIONS

- counting;
- % weight;
- weight totalisation;
- conversion up to 13 units of measure;
- zeroing;
- zero tracking;
- semi-automatic tare;
- digital calibration;
- backlight command;
- low battery warning.

COUNTING FEATURES

- Internal sensitivity and minimum recommended A.P.W.:

Model	HLD1200	HLD3000	HLD6000
Internal sensitivity g	0,0025	0,005	0,014
Min. recommended A.P.W. g	0,02	0,05	0,1

VERSIONS

Available versions

	Codice	Classe	Piatto Max (mm)	Max (g)	d (g)	M (g)*	Linearità (g) +/-	Ripetibilità (g)
	HLD1200	II	140x150 mm	1200	0,02	0,2	0,04	0,02
	HLD3000	II	140x150 mm	3000	0,05	0,5	0,1	0,05
	HLD6000	II	140x150 mm	6000	0,1	1	0,2	0,1

(*) CE-M divisions are obtainable only with the relative options.



MASSAMATIC PTY LTD

13 BOOMPIES STREET - 7500 - PAROW-EAST - SOUTH AFRICA

Tel. 0027-219302510

E-mail sales@massamatic.com

Web www.massamatic.com